

# **KINETIC**<sup>TM</sup>

HI-PERFORMANCE BATTERY



**MAINTENANCE FREE**

# **KINETIC**<sup>TM</sup>

HI-PERFORMANCE BATTERY

## **HEAT SEALED COVER**

No leakage and contamination

## **MAGIC EYE**

Gives an indication to the customer when the battery is discharged



## **FLAME ARRESTER**

Prevents possibility of explosion and prevents any inflow of dust

## **ENVELOPE SEPARATOR**

Improve vibration resistance and avoids internal shorting

## **EXPANDED METAL TECHNOLOGY**

Extra strength, overcharge resistance and resistance to grid corrosion

# **HIGHER CCA + HIGHER RC**

Helps quick cranking hence gives auto electrical longer life.

Gives maximum benefit from battery in times of emergency

**Authorized Distributor/Dealer:**





**KINETIC Maintenance Free Price List**

Sno	Kinetic Part No	Old JIS partno	Dimensions mm			Wt /Battery filled(kgs)	CCA	RC
			L	W	H			
1	36B20R/L	NS40 R/L	197	129	227	9.6	250	39
2	38B20R/L	NS40Z R/L	197	129	227	10.6	320	54
3	32C24R/L	N 40	238	129	225	12	350	73
4	46B24R/L	NS60R/L	238	129	225	12.1	350	73
5	46B24R/L(S)	NS60R/L(S)	238	129	225	12.1	350	73
6	48D26R/L	N50R/L	259	173	227	16.6	360	75
7	55D26R/L	N50ZR/L	259	173	227	16.9	400	85
8	65D26R/L	NS 70 R/L	259	173	227	17.9	500	115
9	80D26R/L	NX-110-5	259	173	227	18.8	505	117
10	65D31R/L	N70 R/L	306	173	225	20.5	510	115
11	75D31 R/L	N 70Z R/L	306	173	225	20.2	550	139
11	95D31R/L	NX-120-7	306	173	225	21.4	640	159
12	95E41R/L	N 100	409	173	233	26.5	700	209
13	115F51R/L	N 120	513	182	248	34	760	212
14	145G51R/L	N 150	510	221	246	41	820	322
15	190H52R/L	N 200	518	274	248	55	850	400

**DIN SERIES**

Sno	Part No		Dimensions mm			Wt /Battery filled(kgs)	CCA	RC
			L	W	H			
1	DIN 44(54434)	DIN 44	207	175	190	12.4	320	56
2	DIN 55(55530)	DIN 55	242	175	190	14.8	410	73
3	DIN66(56638)	DIN 66	278	175	190	17.5	500	91
4	DIN74(57412)	DIN 74	278	175	190	18.7	590	109

\* This price list superceds all other pricelists issued earlier

\* Warranty is discounted in the prices

\* Standard payment terms apply

\* These prices will be valid for Nov 2011 orders