

**CONTROL
PLUS**



AUTHORIZED DISTRIBUTOR/DEALER



POWERED PERFORMANCE

**CONTROL
PLUS**



**18 MONTHS
WARRANTY**

POWERED PERFORMANCE

Features



HEAT SEALED COVER

Prevents leakage and contamination
Adds to case strength and rigidity
Include permanent flame arresters to prevent an accidental explosion from external sparks or flame
Have magic eye in for faster checking



FLAME ARRESTER

Safety system
Prevents possibility of explosion from spark of outside
Minimizes acid-leakage
Prevents inflow of dust



LOW-RESISTANCE ENVELOPE SEPARATION

Encapsulate negative plates
Improve vibration durability
Prevent "treeing" and internal shorting between positive & negative plates



CENTERED CAST - ON - STRAP PLATE

Stronger than the thinner gas burnt conventional connectors
Reduce the lever action movement resulting from road shock



EXPANDED METAL TECHNOLOGY

Offer considerable strength
Resistant to grid corrosion
Over-charge resistant
Minimal gassing and water usage
Less self-discharge
Resist thermal runaway



REINFORCED DESIGN

Reinforced design is precisely tailored to support the battery elements for resistance to vibration and road shock damage. Material is light weight, exceptionally strong, durable and resistant to handling and impact damage

Specification

CONTROL PLUS MAINTENANCE FREE JIS SPECS

S.No.	Part No	CCA SAE Amps	RC Min	Warranty (Months)
1	36B20R	260	46	18
2	38B20R	320	54	18
3	38B20L	320	54	18
4	55B24LS	350	73	18
5	50D26R	360	75	18
6	60D23L	400	93	18
7	60D26R	400	85	18
8	65D26L	500	115	18
9	80D26R	505	117	18
10	70D31R	510	115	15
11	75D31L	550	139	15
12	95D31R	640	159	15
13	CN 100	700	209	15
14	CN 120	760	212	15
15	CN 150	820	322	15
16	CN 200	850	400	15
17	Inverter 120	N/A	N/A	15
18	Inverter 150	N/A	N/A	15
19	Inverter 180	N/A	N/A	15

CONTROL PLUS MAINTENANCE FREE DIN SPECS

S.No.	Part No	CCA SAE Amps	RC Min	Warranty (Months)
1	DIN 44	440	75	18
2	DIN 55	540	91	18
3	DIN 66	640	108	18
4	DIN 88	810	149	18

CONTROL PLUS MOTORCYCLE RANGE

S.No.	Part No	Warranty (Months)
1	CP- 2.5L-C	18
2	CP-5L-B	18
3	CP-9B	18